

### ROUGH OPENINGS

	WIDTH		6-8
S I N G L E	1-6	20"	82½"
	2-0	26"	
	2-6	32"	
	2-8	34"	7-0
	2-10	36"	86½"
3-0	38"		
D O U B L E	3-0	38"	8-0
	4-0	50"	
	5-0	62"	98½"
	5-4	66"	
	6-0	74"	

Double Door With T-Astrigal &/or bolt : Add 3/8" to Width

For Louvered doors: Add 1/4" to Width

### Bifold Finished Openings

	WIDTH		6-8
2  L e a f	2-0	24"	81"
	2-4	28"	
	2-6	30"	
	2-8	32"	7-0
	3-0	36"	85"
4-0	48"		
4  L e a f	4-8	56"	8-0
	5-0	60"	
	5-4	64"	97"
	6-0	72"	

### By-Pass Finished Openings

	WIDTH		6-8
	3-0	35"	81¾"
	4-0	47"	
	5-0	59"	7-0
	5-4	63"	85¾"
	5-8	67"	
6-0	71"	8-0	
3LVS	7-6	88"	97¾"
4LVS	9-0	106"	

Finished opening is from top of finished floor to bottom of finished head.

- × STANDARD UNDERCUT IS 7/8". THIS IS ACCOMPLISHED WITH THE JAMB LEG BEING 7/8" LONGER THAN THE SLAB.
- × DOOR SLABS ARE 3/16" NARROWER THAN NOTED.
- × ALL SLABS ARE SQUARE EDGE NOT BEVELED.